

## TECHNICAL DATA SHEET

# ITR PRIMA XL SYNTHETIC



**ITR PRIMA XL Synthetic**, Top of the line Petrol Engine Oil meeting highest performance long drain premium quality petrol engine oil suitable for Modern cars and Passenger vehicles. ITR PRIMA XL SY 5W- 40 is blended with Highly Refined base stocks and synergistic additive system for outstanding detergency, dispersancy characteristics, anti-wear and antioxidant properties, high viscosity index and low temperature flow properties, ITR PRIMA XL technology provides strong protection for modern FSI, TDI and turbocharged engines.

## PERFORMANCE STANDARDS

### MEETS OR EXCEEDS

- API SN • ACEA A3/B4,
- MB-229.3 • BMW LL-04,
- VW 502.00, VW505.00
- Renault RN 0700/710
- Porsche A40

## TYPICAL CHARACTERISTICS 5W-40

- Kinematic Viscosity @ 40 °C (ASTM D 445): 80-90
- Kinematic Viscosity @ 100 °C (ASTM D 445): 13.5-14.0
- Viscosity Index (ASTM D 2270): >160
- CCS Viscosity (ASTM D 5293): <6600 cP at -30 deg.c
- Pour point (ASTM D 97): <-39
- Flashpoint (ASTM D 92 & 93): >200
- Total Base Number (ASTM D 2896): 8.0-9.0