

ITR SUPER TRACTOR OIL UNIVERSAL

ITR SUPER TRACTOR OIL UNIVERSAL (STOU). It is carefully engineered with selected base stocks and performance additives to meet the diverse performance requirements of Engine, Wet Brakes, Power Take off Clutch, Hydraulic System, Transmission and Final Drive of modern new generation farm tractors. High performance multi-grade oil designed for year-round multipurpose lubrication of the different systems in agricultural tractors and harvesters.

PERFORMANCE STANDARDS

- API CG-4/SF,
- ACEA E2
- API GL-4
- CATERPILLAR TO2
- ALISION C-4

TYPICAL CHARACTERISTICS OF SAE 15W-40

- Kinematic Viscosity @ 40 °C (ASTM D 445): 100-115
- Kinematic Viscosity @ 100 °C (ASTM D 445): 14.5-15.0
- Viscosity Index (ASTM D 2270): MIN 145
- Total Base number (ASTM D 2896): 11.0-12.0
- CCS viscosity (ASTM D-5293): < 7000 cP At -20 deg.c

TYPICAL CHARACTERISTICS OF SAE 10W-30

- Kinematic Viscosity @ 40 °C (ASTM D 445): 70-80
- Kinematic Viscosity @ 100 °C (ASTM D 445): 11.0-12.0
- Viscosity Index (ASTM D 2270): MIN 140
- Total Base number (ASTM D 2896): 11.0-12.0
- CCS viscosity (ASTM D-5293): < 7000 cP At -25 deg.c